

# ADKH series

## Large Dry pumps for Harsh Processes



### AD30KH/40KH/70KH/100KH : ADVANCED SOLUTIONS FOR FPD & SOLAR INDUSTRY

#### Proven technology

Based on the field proven technology developed over the last 15 years for the semiconductor industry, Alcatel proposes a new high capacity dry pump range able to answer the needs of FPD and Solar harsh process applications as PECVD.

This range is composed of 4 versions: AD30KH, AD40KH, AD70KH and AD100KH depending on required pumping speed.

#### Features

- Field proven special materials
- Optional integrated powder trap
- High operating temperatures
- Low energy consumption
- Low noise level
- Low maintenance : typical 1-2 years between overhauls depending on application
- The ADKH range is compatible with Adixen supervision network and predictive maintenance software





#### Benefits

- High reliability on highly corrosive gases as  $NF_3$  cleans
- High reliability even with large quantities of powder
- Avoid condensable by-products inside the pump
- Low CoO
- Compatible with operators based environments
- Low maintenance costs
- Increased up-time, lower scrap risks, lower maintenance costs

#### Applications : FPD, Solar



## Performance



## Technical specifications

CHARACTERISTIC		AD30KH	AD40KH	AD70KH	AD100KH
Peak pumping speed (50/60 Hz)	m <sup>3</sup> / h l / min	1,500 25,000	2,100 (1) 35,000	3,700 61,700	4,800 80,000
Typ. ultimate pressure (no purge) 50/60 Hz	mbar	9.10 <sup>-4</sup> / 0,68		2.10 <sup>-4</sup> / 0,15	
Typ. ultimate pressure (purge 50 slm) 50/60 Hz	mtorr	5.10 <sup>-3</sup> / 3,75		<1.10 <sup>-3</sup> / <0,75	
Maximum continuous inlet pressure (50/60 Hz)	mbar torr	6,3 4,7	2,2 1,7	1,6 1,2	1,3 1
Maximum continuous inlet flow (50/60 Hz)	slm	70	up to 55 slm (2)		70
Power consumption at ultimate pressure	kW	3,5	3	5,2	6,3
Power consumption at maximum inlet flow	kW	8	5,5	8	9,3
Power supply voltage (3 phases)	Volt	208/220 or 380-480V 3 phases 50/60 hz			
Maximum exhaust overpressure	mbar / torr	1 200 / 900			
N2 flowrate range	slm	0 - 120			
Cooling water flow	l / mn	5	3	4	
Water connect		quick connect 3/8"			
Inlet flange		ISO K 160			ISO K 200
Exhaust Flange		ISO KF40			
Noise level ( at ultimate pressure )	dB(A)	< 75			
Dimensions Length x Width x Height	mm	1281x665x985	1281x665x985	1751x899x1537	1751x899x1635
Weight	Kg	695	770	655 + 725	655 + 810

(1) subject to flow limitation. Contact Adixen for further information.

(2) subject to pumping speed reduction. Contact Adixen for further information.



Alcatel Vacuum Technology France  
98, avenue de Brogny - BP 2069 - 74009 ANNECY CEDEX - FRANCE  
Tel.: (33) (0) 4 50 65 77 77 - Fax: (33) (0) 4 50 65 77 89  
www.adixen.com

An Alcatel-Lucent Company

**China**  
Alcatel Vacuum  
Technology Shanghai  
Tel: (8621) 5027 0628  
Fax: (8621) 3895 3815

**France**  
Alcatel Vacuum  
Technology France  
Tel: (33) 04 50 65 77 77  
Fax: (33) 04 50 65 77 89

**Germany**  
Alcatel Hochvakuum  
Technik GmbH  
Tel: (49) 9342 96 10 0  
Fax: (49) 9342 96 10 30

**Italy**  
Alcatel Vacuum  
Systems S.p.A.  
Tel: (39) 039 686 3855  
Fax: (39) 039 667 125

**Japan**  
Alcatel-Lucent Japan Ltd  
Tel: (81) 3 6431 7130  
Fax: (81) 45 544 0049

**Korea**  
Alcatel Vacuum  
Technology Korea  
Tel: (82) 31 206 6277  
Fax: (82) 31 204 6279

**Netherlands**  
Alcatel Vacuum  
Technology Netherlands  
Tel: (31) 345 478 400  
Fax: (31) 345 531 076

**Singapore**  
Alcatel-Lucent Singapore  
Tel: (65) 6254 0828  
Fax: (65) 6254 7018

**Sweden**  
Adixen Sensistor AB  
Tel: (46) 13 35 59 00  
Fax: (46) 13 35 59 01

**Taiwan**  
Alcatel Vacuum  
Technology Taiwan  
Tel: (886) 3 5599 230  
Fax: (886) 3 5599 231

**United Kingdom**  
Alcatel Vacuum  
Technology (U.K.)  
Tel: (44) 1 506 418 000  
Fax: (44) 1 506 418 002

**USA**  
Alcatel Vacuum  
Products  
Tel: (1) 781 331 4200  
Fax: (1) 781 331 4230